

## High expansion braided sleeving black 9 mm

### Information

- Made of sturdy polyester
- Highly flexible
- High rate of expansion
- Easy to apply over irregular shapes
- Good abrasion resistance



### Base Data

|                                 |                                                                                                                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application                     | Helagaine HEGPX is used whenever a higher expansion rate is required. HEGPX is particularly suitable for use in the automotive industry, panel building and in electrical appliances. |
| Application Tool                | HSG0                                                                                                                                                                                  |
| Colour                          | Black (BK)                                                                                                                                                                            |
| Material                        | Polyester (PET)                                                                                                                                                                       |
| Open, post termination (Yes/No) | No                                                                                                                                                                                    |
| Pack Cont.                      | 100m                                                                                                                                                                                  |
| Package Content packed in       | metre                                                                                                                                                                                 |
| PART DESCRIPTION                | HEGPX09-PET-BK                                                                                                                                                                        |
| Part No.                        | 17000090                                                                                                                                                                              |
| Product Family                  | Helagaine HEGPX                                                                                                                                                                       |
| Product Group                   | High-expansion polyester braided sleeving                                                                                                                                             |

### Specifications

|                               |                     |
|-------------------------------|---------------------|
| ELV compliant (Article 4 – 2) | YES                 |
| EN 45545-2 Results            | R22 HL2, R23 HL2    |
| Flammability                  | UL 94 V2, FMVSS 302 |

|                            |                   |
|----------------------------|-------------------|
| Halogenfree                | Yes               |
| Hazardous good             | No                |
| Melting Point              | +250 °C           |
| Operating Temperature – °C | -50 °C to +150 °C |

Specifications



|                |                          |
|----------------|--------------------------|
| Specifications | ANSI/NFPA 70, EN 45545-2 |
|----------------|--------------------------|

|                           |    |
|---------------------------|----|
| UL Listed (US and Canada) | No |
|---------------------------|----|

|             |                      |
|-------------|----------------------|
| UL OCD link | <a href="#">Link</a> |
|-------------|----------------------|

|                               |     |
|-------------------------------|-----|
| UL Recognized (US and Canada) | Yes |
|-------------------------------|-----|

|                |         |
|----------------|---------|
| UL-File Number | E197993 |
|----------------|---------|